




**Introducing our new line of  
Graffiti Protectants!**




**GRIZZLY**

Permanent Anti-Graffiti Coating



**HIPPO SEAL**

Clear Water Repellent




**HIPPO SEAL II**

For Wood and Masonry




*We will make you the  
Graffiti Removal Specialists ...*

**... WITH OUR BATTLE HARDENED  
LINE-UP OF GRAFFITI PROTECTANTS!**



# GRIZZLY

## Permanent Anti-Graffiti Coating



### **NON-SACRIFICIAL ANTI-GRAFFITI COATING**

#### **PRODUCT DESCRIPTION**

Grizzly Non-Sacrificial Anti-Graffiti Coating is a single part system that provides a tough and durable graffiti resistant finish. This is a cross-linking co-polymer material coating that dries clear (non-yellowing) with a low luster sheen. Protects a variety of interior and exterior vertical surfaces from permanent graffiti staining and damage. Will protect your surface from graffiti defacement caused by commercial available spray paints.

#### **Features and Benefits of Grizzly**

Supplied ready to use—no mixing needed

V.O.C. compliant—less than 60 g/l

Treated surfaces will sustain unlimited graffiti removals for a period up to ten years Will retard the growth of mildew, mold, fungus or bacteria

Surfaces require no particular maintenance. No expensive sand blasting needed. Can be applied on all structure surfaces.

#### **Material Application Requirements**

For easy removals of Graffiti for up to ten years on unpainted surfaces:

First apply one coat of HIPPO SEAL Water Repellent

Then apply One Coat of Grizzly for 1 to 2 years of removals

Apply Two Coats of Grizzly for 5 years of removals

Apply Three Coats of Grizzly for 10 years of removals

#### **For painted surfaces:**

Apply One Coat of Grizzly for 1 to 2 years of removals


Apply Two Coats of Grizzly for 5 years of removals

Apply Three Coats of Grizzly for 10 years of removals

#### **Recommended Uses:**

- Concrete, Brick, Stucco
- Stone
- Metal
- Wood
- Plastic
- Aggregate panels
- EIFS and cement plaster
- Water Borne and Solvent Based Coatings
- Previously or newly painted surfaces.





# HIPPO SEAL

## Clear Water Repellent



### **Hippo Seal Concentrate with Micro-Lok** **100% PENETRATING WATER REPELLENT ALKOXYSILOXANE**

#### **PRODUCT DESCRIPTION**

HIPPO-SEAL CONCENTRATE is a solvent free, 100% active solid, Alkoxysiloxane repellent which is to be diluted 9 to 1 with clean water before use, HIPPO-SEAL self emulsifies to form a high performance and deep penetrating, alkali resistant water repellent emulsion. When applied, HIPPO-SEAL forms a short-chain water repellent barrier deep within the masonry surface. This hydrophobic barrier displaces water yet remains highly vapor permeable and allows moisture to escape. HIPPO-SEAL performance is not affected by weathering, UV light or wind driven rain. MICRO-LOK creates a micro-molecular chemical and mechanical bond between the water repellent chemicals and the substrate. HIPPO-SEAL penetrates deep into porous masonry surfaces to provide long lasting and virtually indestructible water repellent protection that is not affected by weather or sunlight. Helps prevent spalling and cracking caused by freeze thaw cycles. Helps prevent chloride ion intrusion and efflorescence.

#### **Product Features**

1. Exclusive MICRO-LOK formulation
2. Mold and Mildew Inhibitor
3. Protection not effected by weathering or UV light
4. Single or multiple coat application
5. V.O.C. compliant
6. Maintenance free
7. Breathable – does not trap moisture
8. Can be used in cold temperature applications
9. Will not yellow.

**Continues to perform: Up to 15 Years**

#### **Recommended Uses:**

- Masonry block
- Concrete
- Stucco
- EFIS or cement plaster
- May be used on composite construction with a variety of substrates.
- An Excellent Primer for Paint Applications
- Recommended for Both Horizontal and Vertical Surfaces
- Oil, Gas and Brake Fluid Repellent





## **Hippo Seal II with Micro-Lok High Performance Masonry and Wood Sealer**

### **PRODUCT DESCRIPTION**

Hippo Seal II is a high performance modified silicone acrylic water repellent and sealer for application on painted and unpainted surfaces.

### **Features and Benefits:**

- Flexible and breathable
- Helps prevent efflorescence
- Protects wood from swelling, shrinking or grain raising.
- Seals and binds chalked surfaces and improves adhesion of topcoat materials.
- May be applied to previously painted and properly prepared surfaces.
- Can be applied to concrete or stucco as a curing agent to promote hardening.

### **HOW TO USE**

Hippo Seal II is supplied ready to use. **DO NOT THIN.** Mix thoroughly prior to use. Avoid application in windy weather. In hot weather, lightly dampen surfaces with clean fresh water to avoid premature or flash drying.

### **Porous Vertical Surfaces**

Start first coat application at the top of the wall. Apply flood coat with a 6"- 8" rundown and backroll material into surface voids. Apply second coat when the first coat is dry.

### **Vertical Concrete Surfaces**

Material may be applied as soon as the forms are removed. Surfaces shall be clean and free of form oils and release agents. Start first coat application at the top of the wall. Apply saturation coat and back-roll materials. Apply second coat when the first coat is dry.

Will seal surface for approximately 3 years

## **CONTACT US!**

**TOLL FREE: 1-866-906-9273**

Graffiti Solutions Canada  
7785 Franktown Rd., Richmond, Ont., K0A 2Z0  
Tel#: (613)838-5842 Fax#: (613)838-5843  
sales@graffitisolutionscanada.com  
www.graffitisolutionscanada.com

